


ACMS40N06D-HF

**N-Channel
RoHS Device
Halogen Free**



Features



- Advanced shielded-gate trench technology.
- Super low on-resistance.
- Fast switching speed.
- Excellent C_{dV}/dt effect decline.
- AEC-Q101 Qualified.

Mechanical data

- Case: TO-252, molded plastic.
- Molding compound: UL flammability classification rating 94V-0.
- Terminals: Matte tin-plated leads, solderability-per MIL-STD-202, method 208.

Circuit Diagram

- G : Gate
- S : Source
- D : Drain



Maximum Ratings (at TA=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-source voltage	V _{DS}	60	V
Gate-source voltage	V _{GS}	±20	V
Continuous drain current (T _c =25°C)	I _D	40	A
Continuous drain current (T _c =100°C)	I _D	33	A
Pulsed drain current (tp= 10μs, T _c =25°C)	I _{DM}	270	A
Single pulse avalanche energy (Note 3)	E _{AS}	53	mJ
Power dissipation (T _c =25°C)	P _D	37	W
Operating junction temperature range	T _J	-55 to +150	°C
Storage temperature range	T _{STG}	-55 to +150	°C

Thermal Characteristics

Parameter	Symbol	Min	Typ	Max	Unit
Thermal resistance junction to case	R _{θJC}		2.4	3.4	°C/W
Thermal resistance junction to air (Note 1)	R _{θJA}		27	35	°C/W

Electrical Characteristics (at TA=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{DSS}	V _{GS} = 0V, I _D = 250μA	60			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = 48V, V _{GS} = 0V			1	μA
Gate-body leakage current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
On Characteristics						
Static drain-source on-resistance (Note 2)	R _{DS(on)}	V _{GS} = 10V, I _D = 20A		7.3	8.5	mΩ
	R _{DS(on)}	V _{GS} = 4.5V, I _D = 15A		10.9	14.5	mΩ
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1	1.72	2.5	V
Gate resistance	R _G	V _{GS} = 0V, f = 1MHz		2.5		Ω
Dynamic Characteristics						
Input capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 15V, f = 1MHz		1430		pF
Output capacitance	C _{oss}			724		
Reverse transfer capacitance	C _{rss}			98.9		
Switching Characteristics						
Turn-on delay time	t _{d(on)}	V _{DD} = 30V, V _{GS} = 15V R _G = 3.3Ω, I _D = 20A		7		ns
Turn-on rise time	t _r			46		
Turn-off delay time	t _{d(off)}			30		
Turn-off fall time	t _f			40		
Total gate charge	Q _g	V _{DD} = 15V, V _{GS} = 10V, I _D = 20A		23.8		nC
Gate to source charge	Q _{gs}			4		
Gate to drain (miller) charge	Q _{gd}			5.4		
Source-Drain Diode Characteristics						
Diode forward voltage (Note 2)	V _{SD}	I _{SD} = 40A, V _{GS} = 0V		0.95	1.2	V
Reverse recovery time	t _{rr}	I _{SD} = 20A, V _{GS} = 0V, d _i /d _t = 100A/μs		37		ns
Reverse recovery charge	Q _{rr}			31		nC

Notes: 1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.

2. The data tested by pulsed, pulse width ≤ 300μs, duty cycle ≤ 2%.

3. The EAS data shows Max. rating. The test condition is V_{DD}=25V, V_{GS}=10V, L=10mH.

Typical Rating and Characteristic Curves (ACMS40N06D-HF)

Fig.1 - Power Dissipation




Fig.2 - Drain Current




Fig.3 - Typical Output Characteristics




Fig.4 - On-Resistance vs. Drain Current and Gate Voltage




Fig.5 - On-Resistance vs. Gate-Source Voltage











Fig.6 - Body-Diode Characteristics




Typical Rating and Characteristic Curves (ACMS40N06D-HF)






Typical Rating and Characteristic Curves (ACMS40N06D-HF)

Fig.13 - Safe Operating Area



Reel Taping Specification




TO-252	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	6.90 ± 0.10	10.50 ± 0.10	2.70 ± 0.10	$1.50 + 0.25$	330 ± 1.00	100 ± 1.00	13.00 ± 0.20
	(inch)	0.272 ± 0.004	0.413 ± 0.004	0.106 ± 0.004	$0.059 + 0.010$	12.992 ± 0.039	3.937 ± 0.039	0.512 ± 0.008

TO-252	SYMBOL	E	F	P	P0	P1	T	W	W1
	(mm)	1.75 ± 0.10	7.50 ± 0.10	8.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	0.30 ± 0.10	$16.00 + 0.30 - 0.20$	21.00 ± 0.30
	(inch)	0.069 ± 0.004	0.295 ± 0.004	0.315 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.012 ± 0.004	$0.630 + 0.012 - 0.008$	0.827 ± 0.012

Marking Code


Part Number	Marking Code
ACMS40N06D-HF	085N06TD



XXX = Control code

Suggested P.C.B. PAD Layout

SIZE	TO-252	
	(mm)	(inch)
A	1.80	0.071
B	2.70	0.106
C	1.50	0.059
D	2.30	0.091
E	6.40	0.252
F	6.80	0.268



Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
TO-252	2,500	13