

The Superior Diodes Solution

10A 60V Schottky Barrier Rectifier RoHS Halogen-Free
Part Numbers: CDBZ31060-HF



Comchip's new Schottky rectifier, CDBZ31060-HF, has a forward current of 10A and reverse voltage of 60V. The surface mount TO-277/Z3 package is leadless, low profile, and ideal for high speed surface mount process. It also fits onto land patterns of TO-277A/B and SMPC packages.

The CDBZ31060-HF features low power loss and high efficiency. The part is REACH and RoHS compliant, Halogen-free, and Lead-free.

- Designed for high speed SMT
- Flat Chip Design
- Low Profile/Leadless Package
- Low Power Loss/High Efficiency
- High Thermal Performance Package

CDBZ31060-HF has a dimension of 6.5 x 4.0 x 1.2 mm and contains a 10A 60V Schottky barrier rectifier chip that offers an operating junction temperature range of -55 to +150°C.

The TO-277/Z3/SMPC package meets UL 94V-0 flammability classification.

The terminals are Matte-Tin plated and solderable per MIL-STD-750, method 2026. High temperature soldering guaranteed: 250°C/10 seconds.

Applications include: Switch Mode Power Supplies, Portable Equipment Battery regulation, High Frequency rectification, DC/DC converters, and as bypass diode for solar panels.



USA

4115 Clipper Court
Fremont, CA 94538, USA
Tel: 510-657-8671
Email: salesusa@comchiptech.com

Taiwan

No. 31, Yong Hsin Lane, Yingtau Rd.,
Yingge Dist., New Taipei City, Taiwan
Tel : 886-2-86776675
Email: salesasia@comchiptech.com

Please contact us for additional information >>>