

<u>10A 45V Schottky Barrier Rectifier RoHS Halogen-Free</u> Part Numbers: CDBZ5T1045-HF



Comchip's new Schottky rectifier, CDBZ5T1045-HF, has a forward current of 10A and reverse voltage of 45V. The surface mount SMC/Z5-T package is leadless, low profile, and ideal for high speed surface mount process.

The CDBZ5T1045-HF features low power loss and high efficiency, with peak forward surge current of 300A. The part is REACH and RoHS compliant, Halogen-free, and Lead-free.

CDBZ5T1045-HF has a dimension of $8.0 \ge 5.0 \ge 1.2$ mm and contains a 10A 45V Schottky barrier rectifier chip that offers an operating junction temperature range of -55 to +150°C.

The SMC/Z5-T package meets UL 94V-0 flammability classification.

The terminals are Matte-Tin plated and solderable per MIL-STD-750, method 2026. High temperature soldering guaranteed: 250°C/10 seconds.

Applications include: Switch Mode Power Supplies, Portable Equipment Battery regulation, High Frequency rectification, DC/DC converters, and as bypass diode for solar panels.

Please contact us for additional information

- Designed for high speed SMT
- Flat Chip Design
- Low Profile/Leadless Package
- Low Power Loss/High Efficiency
- Low Forward Voltage
- High Current Capability
- High Thermal Performance Package



USA

4115 Clipper Court Fremont, CA 94538, USA Tel: 510-657-8671 Email: salesusa@comchiptech.com

Taiwan

No. 31, Yong Hsin Lane, Yingtau Rd., Yingge Dist., New Taipei City, Taiwan Tel : 886-2-86776675 Email: salesasia@comchiptech.com

www.comchiptech.com