


CZRUR2V4B Thru CZRUR39VB

Voltage 2.4 to 39 Volts

Power 150 mWatts

RoHS Device




Features

- 150mW Power Dissipation.
- High Voltages from 2.4 ~ 39 V.
- Designed for mounting on small surface.
- Extremely thin/leadless package.
- Constant voltage control.
- Pb free product.

Mechanical data

- Case: 0603/SOD-523F Standard package
Molded plastic.
- Terminals: Gold plated, solderable per
MIL-STD-750,method 2026.
- Polarity: Indicated by cathode band.
- Weight: 0.003 gram(approx.).



Maximum Rating AND Electrical Characteristics

Parameter	Symbol	Value	Unit
Maximum Forward Voltage Drop at $I_F = 10 \text{ mA}$	V_F	0.9	V
Maximum Power Dissipation at 25°C	P_D	150	mW
Forward current , surge peak 8.3 ms single half sine-wave superimposed on rate load(JEDEC method)	I_{FSM}	2.0	A
Peak ESD voltage capability (IEC 61000-4-2)	V_{PV}	8	kV
Operating Junction and Storage Temperature Range	T_J	-55 to +125	$^\circ\text{C}$

Electrical Characteristics(Ta = 25C) °

Part Number	Marking Code	Zener Voltage			Operating resistance		Rising operating Resistance		Reverse current	
		V _Z (V)			ZZT(Ohm)		ZZK(Ohm)		IR(uA)	
		Min	Max	I _Z (mA)	Max	I _Z (mA)	Max	I _Z (mA)	Max	V _R (V)
CZRUR2V4B	U2	2.34	2.46	5	100	5	1800	0.25	100	1
CZRUR2V7B	U3	2.63	2.77	5	100	5	1900	0.25	75	1
CZRUR3V0B	U4	2.93	3.08	5	95	5	2000	0.25	50	1
CZRUR3V3B	U5	3.22	3.38	5	95	5	2200	0.25	25	1
CZRUR3V6B	U6	3.51	3.69	5	90	5	2300	0.25	15	1
CZRUR3V9B	U7	3.80	4.00	5	90	5	2400	0.25	10	1
CZRUR4V3B	U8	4.19	4.41	5	88	5	2500	0.25	5	1
CZRUR4V7B	U9	4.58	4.82	5	70	5	2200	0.25	3	1.5
CZRUR5V1B	UA	4.97	5.23	5	50	5	2050	0.25	2	2
CZRUR5V6B	UB	5.46	5.74	5	25	5	1800	0.25	2	3
CZRUR6V2B	UC	6.05	6.36	5	10	5	1300	0.25	1	4
CZRUR6V8B	UE	6.63	6.97	5	8	5	750	0.25	1	5.2
CZRUR7V5B	UF	7.31	7.69	5	7	5	600	0.25	0.5	6
CZRUR8V2B	UG	8.00	8.41	5	7	5	600	0.25	0.5	6.5
CZRUR9V1B	UH	8.87	9.33	5	10	5	600	0.25	0.1	7
CZRUR10VB	UJ	9.75	10.25	5	15	5	600	0.25	0.1	8
CZRUR11VB	UK	10.73	11.27	5	18	5	600	0.25	0.1	8.4
CZRUR12VB	UM	11.70	12.30	5	22	5	600	0.25	0.1	9.1
CZRUR13VB	UN	12.68	13.32	5	25	5	600	0.25	0.1	9.9
CZRUR15VB	UP	14.63	15.37	5	32	5	600	0.25	0.1	11
CZRUR16VB	UQ	15.60	16.40	5	36	5	600	0.25	0.1	12
CZRUR18VB	UR	17.55	18.45	5	42	5	600	0.25	0.1	14
CZRUR20VB	US	19.50	20.50	5	48	5	600	0.25	0.1	15
CZRUR22VB	UT	21.45	22.55	5	55	5	600	0.25	0.1	17
CZRUR24VB	UU	23.40	24.60	5	62	5	600	0.25	0.1	18
CZRUR27VB	UV	26.33	27.67	5	70	5	600	0.25	0.1	21
CZRUR30VB	UW	29.25	30.75	5	78	5	600	0.25	0.1	23
CZRUR33VB	UX	32.18	33.82	5	88	5	700	0.25	0.1	25
CZRUR36VB	UY	35.10	36.90	5	95	5	700	0.25	0.1	27
CZRUR39VB	UZ	38.03	39.97	5	130	5	800	0.25	0.1	30

RATING AND CHARACTERISTIC CURVES (CZRUR2V4B Thru CZRUR39VB)




Fig.1 Zener voltage characteristics




Fig.2 Derating curve





Fig.3 Zener voltage-temp. Coefficient characteristics

Reel Taping Specification




0603 (SOD-523F)	SYMBOL	A	B	C	d	D	D ₁	D ₂
	(mm)	1.00 ± 0.10	1.85 ± 0.10	1.00 ± 0.10	1.55 ± 0.05	178 ± 1	60.0 MIN.	13.0 ± 0.20
	(inch)	0.039 ± 0.004	0.073 ± 0.004	0.039 ± 0.004	0.061 ± 0.002	7.008 ± 0.04	2.362 MIN.	0.512 ± 0.008

0603 (SOD-523F)	SYMBOL	E	F	P	P ₀	P ₁	T	W	W ₁
	(mm)	1.75 ± 0.10	3.50 ± 0.05	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	0.23 ± 0.05	8.00 ± 0.20	13.5 MAX.
	(inch)	0.069 ± 0.004	0.138 ± 0.002	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.009 ± 0.002	0.315 ± 0.008	0.531 MAX.

Suggested PAD Layout

SIZE	0603/SOD-523F	
	(mm)	(inch)
A	1.25	0.049
B	0.60	0.024
C	1.00	0.039
D	1.85	0.073
E	0.65	0.026



Standard Package

Case Type	Qty per Reel	Reel Size
	(Pcs)	(inch)
0603/SOD-523F	4000	7