


CPD1E5V0U-D (RoHS Device)



Features

Uni-directional ESD protection

IEC 61000-4-2 ±20kV(air),±15kV(contact).

Working voltage:5V

Ultra small SMD package:0503.

High component density.

Mechanical data


Case:SOD-723F (1308) Standard package ,
molded plastic.

Terminals: Gold plated, solderable per
MIL-STD-750, method 2026.

Marking Code: Cathode band & .E05

Mounting position: Any.

Weight: 0.002 gram (approx.).



Maximum Rating AND Electrical Characteristics (at TA=25 °C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Forward voltage	I _R = 10mA	V _F		0.8		V
Diode breakdown voltage	I _Z = 1mA	V _{BD}	6			V
Leakage current	V _R = 5V	I _L		0.3	2.0	uA
Junction capacitance	V _R = 0V, f = 1MHz	C _T		90	120	pF
Clamping voltage	I _{PP} = 5A, T _P =8/20us I _{PP} = 16A, T _P =8/20us	V _C			9.8 12.5	V
ESD capability	IEC 61000-4-2(air) IEC 61000-4-2(contact)	V _{ESD}			±20 ±15	kV
Peak pulse power		P _{PK}			200	W
Operation temperature		T _J			+125	°C
Storage temperature		T _{STG}	-55		+150	°C

RATING AND CHARACTERISTIC CURVES (CPD1E5V0U-D)

Fig. 1 - 8/20us Peak pulse current waveform acc. IEC 61000-4-5




Fig. 2 - Power rating derating curve




Fig. 3 - Clamping voltage vs. peak pulse current




Fig. 4 - Forward voltage vs. forward current




Fig. 5 - Capacitance between terminals characteristics






Fig. 6 - ESD Clamping (8kv Contant per IEC 61000-4-2)



Reel Taping Specification



SOD-723F	SYMBOL	A	B	C	d	D	D ₁	D ₂
	(mm)	0.90 ± 0.10	1.46 ± 0.10	0.80 ± 0.10	1.55 ± 0.05	178 ± 1	60.0 MIN.	13.0 ± 0.20
	(inch)	0.035 ± 0.004	0.057 ± 0.004	0.031 ± 0.004	0.061 ± 0.002	7.008 ± 0.04	2.362 MIN.	0.512 ± 0.008

SOD-723F	SYMBOL	E	F	P	P ₀	P ₁	T	W	W ₁
	(mm)	1.75 ± 0.10	3.50 ± 0.05	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	0.22 ± 0.05	8.00 ± 0.20	13.5 MAX.
	(inch)	0.069 ± 0.004	0.138 ± 0.002	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.009 ± 0.002	0.315 ± 0.008	0.531 MAX.


Marking Code

Park Number	Marking Code
CPD1E5V0U-D	.E05



Suggested PAD Layout

SIZE	SOD-723F	
	(mm)	(inch)
A	0.85	0.033
B	0.55	0.022
C	0.85	0.033
D	1.40	0.055
E	0.30	0.011



Standard Package

Case Type	Qty per Reel	Reel Size
	(Pcs)	(inch)
SOD-723F	4000	7