


B05S-HF Thru. B10S-HF

Reverse Voltage: 50 to 1000 V

Forward Current: 0.8 A

RoHS Device

Halogen Free




Features

- Rating to 1000V PRV.
- Ideal for printed circuit board.
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product.
- Pb free product.
- UL recognized file # E349301. 

Mechanical data

- Polarity: Symbol molded on body.
- Weight: 0.125 grams.
- Mounting position: Any.



Maximum Rating And Electrical Characteristics

Rating at $T_A=25^{\circ}\text{C}$, unless otherwise noted.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Parameter		Symbol	B05S-HF	B1S-HF	B2S-HF	B4S-HF	B6S-HF	B8S-HF	B10S-HF	Unit
Maximum recurrent peak reverse voltage		V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage		V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage		V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current (Note 1) @T _A =40°C		I _{AV}	0.8							A
Peak forward surge current, 8.3mS single half sine-wave, superimposed on rated load (JEDEC Method)		I _{FSM}	30							A
Peak forward voltage at 0.8A DC		V _F	1.1							V
Maximum DC reverse current at rated DC blocking voltage @T _J =25°C @T _J =125°C		I _R	5.0 500							μA
Typical junction capacitance per element (Note 2)		C _J	15							pF
Typical thermal resistance	junction to ambient	R _{θJA}	125							°C/W
	junction to case	R _{θJC}	75							
Operating temperature range		T _J	-55 to +150							°C
Storage temperature range		T _{STG}	-55 to +150							°C

Notes: 1. Mounted on P.C. Board.
2. Measured at 1.0MHz and applied reverse voltage of 4V DC.

Rating and Characteristic Curves (B05S-HF Thru. B10S-HF)

Fig.1 - Forward Current Derating Curve




Fig.2 - Maximum Non-Repetitive Surge Current




Fig.3 - Typical Reverse Characteristics




Fig.4 - Typical Forward Characteristics






Fig.5 - Typical Junction Capacitance



Reel Taping Specification




MBS	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	4.90 ± 0.10	7.24 ± 0.10	3.33 ± 0.10	1.55 ± 0.05	330	50.0 MIN.	13.00 ± 0.20
	(inch)	0.193 ± 0.004	0.285 ± 0.004	0.131 ± 0.004	0.061 ± 0.002	13	1.969 MIN.	0.512 ± 0.008

MBS	SYMBOL	E	F	P	P0	P1	T	W	W1
	(mm)	1.75 ± 0.10	5.50 ± 0.05	8.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	0.30	12.00 ± 0.30	12.00~14.40
	(inch)	0.069 ± 0.004	0.217 ± 0.002	0.315 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.012	0.472 ± 0.012	0.472~0.657

Marking Code


Part Number	Marking code
B05S-HF	B05S
B1S-HF	B1S
B2S-HF	B2S
B4S-HF	B4S
B6S-HF	B6S
B8S-HF	B8S
B10S-HF	B10S



X / XX = Product type marking code

Suggested P.C.B. PAD Layout

SIZE	MBS	
	(mm)	(inch)
A	0.82MIN	0.032MIN
B	2.55REF	0.100REF
C	0.92MIN	0.036MIN
D	7.00MAX	0.276MAX



Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
MBS	3,000	13