


CPDZD3V3-HF

RoHS Device
Halogen Free




Features

- Bi-directional ESD protection of one line.
- Reverse stand-off voltage: 3.3V.
- Low reverse clamping voltage.
- Low leakage current.
- Excellent package: 0.6mm x 0.3mm x 0.31mm.
- Fast response time.
- JESD22-A114-B ESD rating of class 3B per human body model.

Mechanical data

- Case: DFNWB0.6x0.3-2L package, molded plastic.
- Mounting position: Any.

Circuit Diagram



Maximum Rating (at $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
IEC 61000-4-2 ESD voltage air model	ESD (Note 1)	± 30	kV
IEC 61000-4-2 ESD voltage contact model		± 16	
JESD22-A114-B ESD voltage per human body model		± 0.4	
ESD voltage machine model			
Peak pulse power (Note 2)	P_{PP}	144	W
Peak pulse current (Note 2)	I_{PP}	16	A
Lead solder temperature - maximum (10 second duration)	T_L	260	$^{\circ}\text{C}$
Operation junction and storage temperature range	T_J, T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Device stressed with ten non-repetitive ESD pulses.

2. Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC 61000-4-5.

Electrical Characteristics (at $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Reverse stand off voltage (Note 1)		V_{RWM}			3.3	V
Reverse leakage current	$V_{RWM} = 3.3\text{V}$	I_R		0.01	0.5	μA
Breakdown voltage	$I_T = 1\text{mA}$	V_{BR}	3.8			V
Clamping voltage (Note 2)	$I_{PP} = 1\text{A}$	V_C		5.8		V
	$I_{PP} = 16\text{A}$			8.5	9	V
Junction capacitance	$V_R = 0\text{V}$, $f = 1\text{MHz}$	C_J		34	42	pF

Notes: 1. Other voltages available upon request.

2. Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC 61000-4-5.

Typical Rating and Characteristic Curves (CPDZD3V3-HF)

Fig.1 - 8/20 μs Peak Pulse Current Waveform Acc. IEC 61000-4-5




Fig.2 - Reverse Characteristics




Fig.3 - Capacitance Characteristics







Fig.4 - V_C — I_{PP}



Reel Taping Specification



DFNWB 0.6x0.3-2L	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	0.41 Typ	0.70 Typ	0.38 Typ	1.50 Typ	178 Typ	54.40 Typ	13.00 Typ
	(inch)	0.016 Typ	0.028 Typ	0.015 Typ	0.059 Typ	7.008 Typ	2.142 Typ	0.512 Typ

DFNWB 0.6x0.3-2L	SYMBOL	E	F	P	P0	P1	W	W1
	(mm)	1.75 Typ	3.50 Typ	2.00 Typ	4.00 Typ	2.00 Typ	8.00 Typ	12.30 Typ
	(inch)	0.069 Typ	0.138 Typ	0.079 Typ	0.157 Typ	0.079 Typ	0.315 Typ	0.484 Typ


Marking Code

Part Number	Marking Code
CPDZD3V3-HF	T3



Suggested P.C.B. PAD Layout

SIZE	DFNWB0.6x0.3-2L	
	(mm)	(inch)
A	0.20	0.008
B	0.22	0.009
C	0.36	0.014
D	0.40	0.016



Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
DFNWB 0.6x0.3-2L	10,000	7