

CPDUT18VMUHT-HF

RoHS Device

Halogen Free




Features

- ESD/Surge protection for 1 line with Unidirectional.
- Protect one I/O line or one power line.
- Fast turn-on and low clamping voltage.
- IEC 61000-4-2 (ESD) ± 30 kV (air/contact)
- IEC 61000-4-4 (EFT) 80A (5/50ns)
- IEC 61000-4-5 (Lightning) 40A (8/20 μ s)

Mechanical data

- Case: DFN1610-2L package, molded plastic.
- Polarity: Indicated by cathode band.
- Mounting position: Any.

Circuit Diagram



Maximum Rating (at TA=25°C unless otherwise noted)

Parameter	Conditions	Symbol	Value	Unit
Peak pulse power	$T_P = 8/20\mu s$	P_{PP}	1320	W
Peak pulse current	$T_P = 8/20\mu s$	I_{PP}	40	A
ESD capability	IEC 61000-4-2(air) IEC 61000-4-2(contact)	ESD	± 30	kV
Operating temperature range		T_J	-55 to +125	°C
Storage temperature range		T_{STG}	-55 to +150	°C

Electrical Characteristics (at TA=25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Working peak reverse voltage		V_{RWM}			18	V
Forward voltage	$I_F = 15mA$	V_F	0.5		1.2	V
Reverse leakage current	$V_{RWM} = 18V$	I_R			0.1	μA
Breakdown voltage	$I_T = 1mA$	V_{BR}	18		22	V
Clamping voltage	$I_{PP} = 5A, T_P = 8/20\mu s$	V_C		23		V
	$I_{PP} = 40A, T_P = 8/20\mu s$	V_C		31	33	
Clamping voltage	$TLP = 16A, T_P = 0.2/100ns$	V_C		23		V
Junction capacitance	$V_R = 0V, f = 1MHz$	C_J		255		pF

Typical Rating and Characteristic Curves (CPDUT18VMUHT-HF)

Fig.1 - 8/20μs Peak Pulse Current Waveform Acc. IEC 61000-4-5




Fig.2 - Power Rating Derating Curve




Fig.3 - Typical Clamping Voltage vs. Peak Pulse Current




Fig.4 - Typical Capacitance Between Terminals Characteristics






Fig.5 - TLP- Positive Pulse



Reel Taping Specification



DFN1610-2L	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	1.20 ± 0.15	1.84 ± 0.11	0.80 + 0.15 - 0.22	1.50 + 0.15 - 0.10	181.00 Max	55.00 ± 5.00	13.00 + 0.50 - 0.20
	(inch)	0.047 ± 0.006	0.072 ± 0.004	0.031 + 0.006 - 0.009	0.059 + 0.006 - 0.004	7.126 Max	2.165 ± 0.197	0.512 + 0.020 - 0.008

DFN1610-2L	SYMBOL	E	F	P	P0	P1	T	W	W1
	(mm)	1.75 ± 0.10	3.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	0.215 ± 0.065	8.00 + 0.30 - 0.20	11.60 Max
	(inch)	0.069 ± 0.004	0.138 ± 0.004	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.008 ± 0.003	0.315 + 0.012 - 0.008	0.457 Max


Marking Code

Park Number	Marking Code
CPDUT18VMUHT-HF	18P



Suggested P.C.B. PAD Layout

SIZE	DFN1610-2L	
	(mm)	(inch)
A	0.60	0.024
B	1.00	0.039
C	0.60	0.024
D	1.80	0.071



Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
DFN1610-2L	3,000	7