


CMSP3139KH3-HF

P-Channel

RoHS Device

Halogen Free





Features

- Surface mount package.
- P-Channel switch with Low $R_{DS(on)}$.
- Operated at low logic level gate drive.

Mechanical data

- Case: SOT-523, molded plastic.
- Mounting position: Any.

Circuit Diagram



Maximum Ratings (at $T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	-20	V
Typical gate-source voltage	V_{GS}	± 12	V
Continuous drain current (Note 1)	I_D	-0.66	A
Pulsed drain current @ $t_p=10\mu\text{s}$	I_{DM}	-1.2	A
Power dissipation (Note 1)	P_D	150	mW
Thermal resistance, junction to ambient (Note 1)	$R_{\theta JA}$	833	$^\circ\text{C/W}$
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$
Lead temperature for soldering purpose (1/8" duration for 10s)	T_L	260	$^\circ\text{C}$

Electrical Characteristics (at Ta=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Static characteristics						
Drain-source breakdown voltage	BV _{DSS}	V _{GS} = 0V, I _D = -250μA	-20			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = -20V, V _{GS} = 0V			-1	μA
Gate-body leakage current	I _{GSS}	V _{GS} = ±10V, V _{DS} = 0V			±20	μA
Gate threshold voltage (Note 2)	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-0.35		-1.1	V
Drain-source on-state resistance (Note 2)	R _{DS(on)}	V _{GS} = -4.5V, I _D = -1A		450	520	mΩ
		V _{GS} = -2.5V, I _D = -0.8A		570	700	
		V _{GS} = -1.8V, I _D = -0.5A		950		
Forward transconductance (Note 2)	g _{fs}	V _{DS} = -10V, I _D = -0.54A		1.2		S
Drain forward voltage	V _{SD}	I _S = -0.5A, V _{GS} = 0V			-1.2	V
Dynamic characteristics (Note 4)						
Input capacitance	C _{iss}	V _{DS} = -16V, V _{GS} = 0V, f = 1MHz		113	170	pF
Output capacitance	C _{oss}			15	25	
Reverse transfer capacitance	C _{rss}			9	15	
Switching characteristics (Note 4)						
Turn-on delay time (Note 3)	t _{d(on)}	V _{GS} = -4.5V, V _{DS} = -10V I _D = -200mA, R _{GEN} = 10Ω		9		nS
Turn-on rise time (Note 3)	t _r			5.8		
Turn-off delay time (Note 3)	t _{d(off)}			32.7		
Turn-off fall time (Note 3)	t _f			20.3		

- Notes: 1. Surface mounted on FR4 board using the minimum recommended pad size.
 2. Pulse width = 300 μs , duty cycle = 2%.
 3. Switching characteristics are independent of operating junction temperatures.
 4. Guaranteed by design, not subject to production.

Typical Rating and Characteristic Curves (CMSP3139KH3-HF)

Fig.1 - Output Characteristics




Fig.2 - Transfer Characteristics




Fig.3 - $R_{DS(ON)}$ — I_d




Fig.4 - On-Resistance vs. Gate to Source Voltage




Fig.5 - I_s — V_{SD}






Fig.6 - Threshold Voltage



Reel Taping Specification




SOT-523	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	1.85 ± 0.05	1.85 ± 0.05	0.875 ± 0.05	1.50 ± 0.10	178.00 ± 2.00	54.40 ± 1.00	13.00 ± 1.00
	(inch)	0.073 ± 0.002	0.073 ± 0.002	0.034 ± 0.002	0.059 ± 0.004	7.008 ± 0.079	2.142 ± 0.039	0.512 ± 0.039

SOT-523	SYMBOL	E	F	P	P0	P1	W	W1
	(mm)	1.75 ± 0.10	3.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	8.00 + 0.30 - 0.10	12.30 ± 1.00
	(inch)	0.069 ± 0.004	0.138 ± 0.004	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.315 + 0.012 - 0.004	0.484 ± 0.039


Marking Code

Part Number	Marking Code
CMSP3139KH3-HF	39K



Suggested P.C.B. PAD Layout

SIZE	SOT-523	
	(mm)	(inch)
A	0.60	0.024
B	0.50	0.020
C	0.40	0.016
D	1.00	0.039
E	1.24	0.049



Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
SOT-523	3,000	7