


CPDWL3V3MHT-HF

Ultra small SMD package

RoHS Device

Halogen Free




Features

- Bi-directional ESD protection.
- High ESD protection level.
- Surface mount package.
- High component density.
- Low clamping voltage.
- Low leakage.
- Working voltage: 3.3V.

Mechanical data

- Case: 01005 package, molded plastic.
- Mounting position: Any.

Circuit Diagram



Maximum Rating (at $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Conditions	Symbol	Value	Unit
Peak pulse power	$T_P = 8/20\mu\text{s}$	P_{PP}	117	W
Peak pulse current	$T_P = 8/20\mu\text{s}$	I_{PP}	13	A
ESD capability	IEC 61000-4-2(air) IEC 61000-4-2(contact)	ESD	± 30	kV
Operating temperature range		T_j	-40 to +125	$^\circ\text{C}$
Storage temperature range		T_{STG}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics (at $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Working peak reverse voltage		V_{RWM}			3.3	V
Breakdown voltage	$I_R = 1\text{mA}$	V_{BR}	4.5			V
Reverse leakage current	$V_R = 3.3\text{V}$	I_R		1	100	nA
Clamping voltage	$I_{PP} = 5\text{A}, T_P = 8/20\mu\text{s}$	V_C		5.0	6.5	V
	$I_{PP} = 13\text{A}, T_P = 8/20\mu\text{s}$			7.0	9.0	
Junction capacitance	$V_R = 0\text{V}, f = 1\text{MHz}$	C_J		14		pF

Typical Rating and Characteristic Curves (CPDWL3V3MHT-HF)

Fig.1 - 8/20μs Peak Pulse Current
Waveform Acc. IEC 61000-4-5




Fig.2 - Power Rating Derating Curve




Fig.3 - Typical Clamping Voltage vs.
Peak Pulse Current









Fig.4 - Typical Capacitance Between
Terminals Characteristics



Reel Taping Specification



01005	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	0.27 ± 0.02	0.49 ± 0.02	0.215 ± 0.02	$1.50^{+0.10}_{-0.00}$	178.00 ± 1.00	60.00 ± 0.50	13.00 ± 0.50
	(inch)	0.011 ± 0.001	0.019 ± 0.001	0.008 ± 0.001	$0.059^{+0.004}_{-0.000}$	7.008 ± 0.039	2.362 ± 0.020	0.512 ± 0.020

01005	SYMBOL	E	F	P	P0	P1	T	W	W1
	(mm)	1.75 ± 0.10	3.50 ± 0.05	2.00 ± 0.05	4.00 ± 0.10	2.00 ± 0.05	0.20 ± 0.05	$8.00^{+0.30}_{-0.10}$	11.50 ± 0.50
	(inch)	0.069 ± 0.004	0.138 ± 0.002	0.079 ± 0.002	0.157 ± 0.004	0.079 ± 0.002	0.008 ± 0.002	$0.315^{+0.012}_{-0.004}$	0.453 ± 0.020


Marking Code

Part Number	Marking Code
CPDWL3V3MHT-HF	D



Suggested P.C.B. PAD Layout

SIZE	01005	
	(mm)	(inch)
A	0.12	0.005
B	0.17	0.007
C	0.17	0.007
D	0.46	0.018



Standard Packaging

Case Type	REEL PACK	
	REEL (pcs)	Reel Size (inch)
01005	10,000	7